



Resin Bonded Filter Cartridge
Designer-Manufacturer-Exporter-Supplier





Resin Bonded Filter Cartridge

Resin Bonded Cartridge is produced from cellulose fibers, which have been intrinsically bonded together by a melamine resin, to create a solid highly durable & porous structure. By treating the fibers in this fashion we can ensure a stronger cartridge that is less likely to collapse than a wound or pleated cartridge.

Features & Benefits

- Free of surfactants, binders and adhesives
 - Excellent flow with low pressure drop
 - High dirt holding capacity
 - Temperature limit 4.4 Deg C to 93.3 Deg C
 - Longer service life
-

Technical Specifications

- Standard Sizes 10", 20", 30" 40"
 - Micron Rating 1, 5, 10, 25
 - Outside Diameter 64mm
 - Inner Diameter 28 mm
-

Applications

- Food & Beverages Bottled water, Flavors, Polishing Lines
- Pharmaceuticals Base product clarifications, Membrane prefilter
- Fine Chemicals Solvents, Process Streams, Water Purification
- Petrochemicals Water flood, Completion Fluids, Amines
- Cosmetics Alcohols, Essential oils, Water lines
- Water Treatment Membrane Protection, Resin Trap
- Metal Finishing Plating solution, paints and resins, products Wash
- Edible Oil
- Mineral Oil
- Paints & Inks
- Resins
- Gasoline
- Alcohols
- Photographic solutions



Designed By: e-brandstudio.com

Filter Concept Pvt. Ltd.

(An ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 Certified Company)

Corporate Office

302, "Aalin", Opp.Gujarat Vidhyapith,
B/h. Jet Airways Office, Ashram Road, Ahmedabad - 14.
Gujarat, INDIA.

Phone : +91-79-2754 1602, 2754 0069, 3291 8518

Fax : +91-79-2754 0801

E-mail : info@filter-concept.com

Manufacturing Unit

A-6, Pushparaj Industrial Estate,
Nutan Mill Compound, B/h. City-Gold Theatre, Saraspur,
Ahmedabad-380018. Gujarat, INDIA.

Phone : +91 -79 -2220 1921, 2220 1292

Fax : +91-79-2220 1911

E-mail : factory@filter-concept.com