





## Basket Filter & Strainer

Designer-Manufacturer-Exporter-Supplier





## Basket Filter & Strainer

Basket filters & strainers will permit the straining & filtering of a wide variety of fluids, to retain solids of almost any size. All baskets are easily removable & cleanable. Basket strainer elements can be offered in single cylinder, double cylinder, multi cylinder & pleated design depending upon requirement of application. They are constructed of filter housing, filter element supported with perforated cage, positive sealing arrangement to avoid any bypass & choice of end connections.

## Operation

Unfiltered liquid enters the basket housing and passes down through them. Solids are retained inside / outside of basket depending upon design and are removed when the unit is serviced. They are available with insitu backwashing arrangement, wherein removal of baskets for cleaning is not required often.

Basket filters & strainers are normally supplied with spring arrangement at the top of filter element. This will ensure any type of bypassing & confirm the position of basket, even in case of reverse flow. Fluid bypass around the basket is prevented by an optional O'-Ring seal between the basket rim and the housing inside diameter.

## Features & Benefits

- Large-area, heavy-duty baskets
- Low pressure drops
- Housing are permanently piped
- Covers are O'-Ring sealed
- Carbon steel, or stainless steel (304 Or 316) housing
- Easy to clean
- Option of insitu backwashing
- Filtration rating from 1 Micron to 2000 micron & more
- ASME code stamp & PED certification available
- High pressure rating design available
- Flow rate up to 2000 m3/hr & More
- Customized design available
- All housings made from SS 316 L, SS 316 & SS304 are mirror polished to resist adhesion of dirt and scale
- Carbon steel housings are sand blasted, Epoxy coated & finally painted with two coats of synthetic enamel
- Liquid displacers for easier servicing
- Duplex / Triplex & Jacketed units available
- High temperature & high pressure design are available
- Normally designed for free flow area through screen, 4 – 6 times pipe flow area
- Choice of basket filter elements
  - Single cylinder design
  - Double cylinder design
  - Multi cylinder design
  - Pleated element design available for low pressure drop & high dirt hold

## Duplex Basket Filter & Strainer

Duplex basket filter & strainer permits continuous operation because flow can be switched back and forth between two filter sections. This allows one side to be serviced while the other is in use. Normally duplex basket filters are separated with three way ball valves or two way ball valve/ butterfly valve connected with equalization tee, between two baskets filter housing.

## Technical Specifications

Sizes : 1" Line Size To 24" Line Size & More

Flow Rate : Capacity: Up to 2000 m3 /hr & More

### Material of Construction

- SS 316L, SS 316, SS 304, SS Duplex,
- CS (ALL GRADE)
- MILD STEEL, ALLOY METALS
- POLYPROPYLENE
- LEAD LINING with Any Metal
- RUBBER LINING with Any Metal
- PTFE LINING with Any Metal
- Glass Flake Coating

### Basket Element Design Available

- Single Cylinder Design | Double Cylinder Design
- Multi Cylinder Design | Pleated Element Design

### Gasket / O' Ring Material

- Neoprene, Nitrile, Silicone, Viton, Buna N, EPDM PTFE

### Choice of Valve Available


- Two way Ball Valve | Three Way Ball Valve
- Butterfly Valve

### End Connections Available

- NPT / BSP Threaded
- Flanged Table E / Table F
- ANSI B 16.5 Flanged
- DIN Standard
- Tri Clover Adaptors
- SMS / Dairy End Connection

## Applications

- Power Plant
- Process Industries
- Cement Plant
- Steel
- Petrochemicals
- FertilizersRefineries
- Oil & Gas
- Chemicals
- Textiles
- & More





Designed By: e-brandstudio.com

## Filter Concept Pvt. Ltd.

(An ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 Certified Company)

### Corporate Office

302, "Aalin", Opp.Gujarat Vidhyapith,  
B/h. Jet Airways Office, Ashram Road, Ahmedabad - 14.  
Gujarat, INDIA.

Phone : +91-79-2754 1602, 2754 0069, 3291 8518

Fax : +91-79-2754 0801

E-mail : [info@filter-concept.com](mailto:info@filter-concept.com)

### Manufacturing Unit

A-6, Pushparaj Industrial Estate,  
Nutan Mill Compound, B/h. City-Gold Theatre, Saraspur,  
Ahmedabad-380018. Gujarat, INDIA.

Phone : +91 -79 -2220 1921, 2220 1292

Fax : +91-79-2220 1911

E-mail : [factory@filter-concept.com](mailto:factory@filter-concept.com)