





Filter Concept Offers Corrosion resistant Fiber Reinforced Plastic (FRP) Filter housing to meet the demanding needs of industry to Filter corrosive and non-corrosive fluids for various applications including Chemicals, Oil and Gas, Petrochemical, Power Generation, Desalination, Potable Water, Municipal and many more Industries.

## Operation

Contaminated fluid enters the housing and is distributed evenly around the filter cartridges/Filter Bags. Filtration takes place from outside to inside or Inside to outside depending upon flow patterns. Solids are collected on the outside of filter cartridges or Inside of the Filter Bags & clear filtrate is collected at outlet.

## Features & Benefits

- Cost effective for Installation
- Low maintenance compared with other materials
- Excellent chemical resistance
- Easy to repair in case of accidental damage
- Light Weight & Long Life

## Special Options

- Customized design available
- Positive sealing arrangement to avoid bypassing
- ASME Designs available

## Technical Specifications

### Sizes (FRP/GRP housings suitable for Cartridge Filter)

- 1 No. To 250 Nos. Of Cartridges in Single Housing
- 2", 2.5", 4", 6" & 8" Diameter of Cartridge
- 10", 20", 30", 40", 50" & 60" Length of Filter cartridge

### Sizes (FRP/GRP filter housings suitable for Bag Filter)

### FRP/GRP Bag filter system suitable for

- 04" x 10" Long Filter Bag
- 04" x 17" Long Filter Bag
- 07" x 17" Long Filter Bag
- 07" x 32" Long Filter Bag

### Multiple bag filter system suitable for

- 2 Nos. Of 07" x 32" Long Filter Bag
- 3 Nos. Of 07" x 32" Long Filter Bag
- 4 Nos. Of 07" x 32" Long Filter Bag
- 5 Nos. Of 07" x 32" Long Filter Bag
- 6 Nos. Of 07" x 32" Long Filter Bag
- 7 Nos. Of 07" x 32" Long Filter Bag
- 8 Nos. Of 07" x 32" Long Filter Bag
- 9 Nos. Of 07" x 32" Long Filter Bag

### Flow Rate

- Capacity: Up to 1000 m<sup>3</sup> / hr & more

### Material of construction

- Fiber Reinforced Plastic (FRP)
- Glass fiber Reinforced Plastic (GRP)
- POLYPROPYLENE

### Cartridge filter housing suitable for filter cartridges of

- Double Open End (DOE) Type
- Code 7 (226 O' Ring) Design
- Code 3 (222 O' Ring) Design
- NPT Threaded Connection Type

### Gasket / O Ring Material

- Neoprene
- Nitrile
- Silicone
- Viton
- Buna N
- EPDM
- PTFE
- Spiral Wound
- CAF

### End connections available

- NPT / BSP Threaded
- Flanged Table E / Table F
- ANSI B 16.5 Flanged
- DIN Standard

## Applications

- Chemicals
- Pharmaceuticals
- Water Treatment
- Coolants
- Paints & Inks
- Food & beverages
- Bore Well water
- Dairy
- Dyes & Intermediates
- RO Pre filtration
- Processing Chemicals
- & Many More



## Filter Concept Pvt. Ltd.

ISO 9001 : 2008  
ISO 14001: 2004  
OHSAS : 18001 : 2007

CE  
ASME 'U' Stamp  
ASME 'UM' Stamp

The National Board Of Boiler  
& Vessel Inspectors 'R' & NB  
Certified Company

### Corporate Office

302, "Aalin", Opp.Gujarat Vidhyapith,  
B/h. Jet Airways Office, Ashram Road,  
Ahmedabad - 14.Gujarat, INDIA.  
Phone : +91-79-2754 1602, 2754 0069, 3291 8518  
Fax : +91-79-2754 0801  
E-mail : [info@filter-concept.com](mailto:info@filter-concept.com),

### Manufacturing Unit

A-6, Pushparaj Industrial Estate,  
Nutan Mill Compound, B/h. City-Gold Theatre, Saraspur,  
Ahmedabad-380018. Gujarat, INDIA.  
Phone : +91 -79 -2220 1921, 2220 1292  
Fax : +91-79-2220 1911  
E-mail : [factory@filter-concept.com](mailto:factory@filter-concept.com)